



Power Wing Work Gripper

PWS06

Inner Diameter Pull Lock Work Gripper

PUES06

Suitable for 3 to 5-Axis Machines!







PUES06



Feature 1.

■PWS06

Supply stable clamping by pull back the workpiece. Suitable for rough machining, OP-10 or OP-20.

■PUES06

Pull back and clamping the inner diameter of workpiece. Suitable for finish machining with stable machining accuracy.


Feature 2.


- Built-in cylinder enables the cost reduction!
 No need to introduce seperated actuator.
- Available on the standard column of machine. Total height is reduced by built-in cylinder.
- Available to be mounted on NC Rotary Table.

Specifications

M	Model	Plunger Stroke _{mm}	Jaw Stroke (diameter)	Gripping Force kN(kgf)		Maximum working pressure MPa (kgf/cm²)		Max. allowable Pressure	Gripping range mm			Weight (with standard soft jaw)	Air consumption
101				Pneumatic at 0.6MPa(6kgf/cm²)	Hydraulic at 1.3MPa (13kgf/cm²)	Pneumatic	Hydraulic		External dam	neter Interr	nal diameter	(will stallded soft Jaw)	(N L)
P۱	WS06	11.4	7.9	29 (2957)	53 (5404)	0.7(7)	1.3(13)	0.2(2)	φ12.7-1	20 φ	70-152	24	0.54
M	Model	Plunger Stroke _{mm}	Jaw Stroke (diameter)	Gripping Force kN(kgf)		Maximum working pressure MPa (kgf/cm²)		Min. allowable Pressure				Weight (with standard soft jaw)	Air consumption
1010				Pneumatic at 0.6MPa(6kgf/cm²)	Hydraulic at 1.3MPa (13kgf/cm²)	Pneumatic	Hydraulic	MPa (kgf/cm ²)	Master Jaw S	Standard Jaw		(willi staillaid soit jaw) kg	(N l)
PU	ES06	10	4.8	26.7 (2724)	58 (5918)	0.7(7)	1.3(13)	0.2(2)	φ 44-70	⊅ 70-89	φ 89-105	21	0.54

WS06 P





Machine Tool Accessories

http://www.mta.kiw.co.jp/

KITAGAWA IRON WORKS CO., LTD.

77-1 Motomachi, Fuchu-shi, Hiroshima-pref. 726-8610, Japan TEL +81 847-40-0526 FAX +81 847-45-8911

- Specifications and outside appearance are subject to change without notice due
- to ongoing research and development.

 The colour of the actual product may be different from the catalogue's due to printing matters.
- Catalogue contents as of 2011.9

 The products herein are controlled under Japanese Foreign Exchange and Foreign Trade Control Act. In the event of importing and/or exporting the products, you are obliged to consult KITAGAWA as well as your government for the related regulation prior to any transaction.