

Specifications

		KRHS315P	KRHS 520D	KRHS 528C	KRHS 930	KRHS 839
Clamping Ranges without chip guard	U1	40	45	70	90	80
	U2	85	100	150	300	190
Max. axial Opening	U	220	236	322	303	402
Clamping range with Chip guard	U1	40	45	70	90	80
	U2	85	100	150	300	190
	U	220	236	322	303	380
Eccentric throw (R value)	R	110	120	155	150	195
Cylinder bore.	d	80	80	80	80	80
Hyd.Connection. (BSP)	e	¼ "	¼ "	¼ "	3/8 "	3/8 "
Lubrication ports	g	M8X1	M8X1	M 10X1	M 10X1	M 10X1
Standard Operating Pressure	bar	5-30	5-40	5-55	5-55	5-55
Max. Operating pressure	bar	35	45	60	60	60
Clamping press./roller at 6 bar	daN	100	100	100	100	100
Max. clamping pressure/roller.	daN	500	1000	1400	1400	1400
Centering accuracy over the whole clamping range.	mm	0.04	0.05	0.05	0.05	0.05
Repeatability	mm	0.01	0.01	0.01	0.01	0.01
Max .Peripheral speed.	m/mi	500	525	350	350	350
Max. Peripheral speed at half max. clamping press.	m/mi	850	865	850	850	850
Weight Approx.	kg.	50	70	150	185	190